

Dual Cylindrical Tanks

ASME CODE SECTION VIII, Division 1

- Powder coated
- With valve plate
- Mounted on brackets
- Designed to facilitate assembly
- You can order in 2 version : AS (American Standard) mounted on brackets / legs or ES (European Standard) heavy duty frame with belts.



Dual Tanks dedicated specifically for:

Dodge Grand Caravan (2008-present), Dodge Caravan (2008-present),
 Dodge RAM VAN (2008-present),
 Chrysler Grand Voyager (2008-present), Chrysler Voyager (2008-present),
 Chrysler Town&Country (2008-present), Volkswagen Routan (2008-present),

- ASME CODE SECTION VIII, Division I
- Powder coating
- With valve plate
- Service Pressure 312 PSI
- Mounted on brackets
- Designed to facilitate assembly



	Diameter D inch	Diameter D mm	Length L inch	Length L mm	Capacity GAL	Capacity L	PSI	80 % Capacity GAL	80 % Capacity L
CT244-1158	9,6	244	45,6	1158	25,62	97	312	20,49	77,6

Dual Tanks dedicated specifically for:

Ford F150, Ford F 250 , Ford F 350, GMC, Chevrolet, Mopar trucks and other North American Truck brands and SUV's*

- ASME CODE SECTION VIII, Division I
- Powder coating
- With valve plate
- Service Pressure 312PSI
- Mounted on brackets
- Designed to facilitate assembly



	Diameter D inch	Diameter D mm	Length L inch	Length L mm	Capacity GAL	Capacity L	PSI	80 % Capacity GAL	80 % Capacity L
DCT315-0813	12,4	315	32	813	30	110	312	24	88
DCT315-0864	12,4	315	34	864	32	120	312	25,6	96

